

Tool Specifications		
Name	SPITFIRE P370 SINGLE SHOT	SPITFIRE P370 WITH MAGAZINE
Impact force	340 J	340 J
Weight	2.8 kg	3.2 kg
Overall dimension L x D x H	435 x 69 x 208 mm	450 x 69 x 240 mm
Cartridge caliber	6.3/10 (10 loads in disc)	6.3/10 (10 loads in disc)
Disc loads colours	Brown, green, yellow, red	Brown, green, yellow, red
Nail capacity	1 in pin guide	10 in magazine (1 strip)
Fastener lengths	15 - 70mm (80 & 90 if pre-driven)	15 - 60mm collated

Characteristics

Automatic piston return by rubber spring

Universal fully automatic tool (1 nail per second with magazine)

Power adjustment by wheel with indicator

Different nose adaptors for different applications

Safety Specifications

C.I.P agreement 001137 / BSI Kitemark agreement KM05325

Indirect action class A1 (A*), velocity < 100 m/s

Complete contact pressure necessary to generate the shot

Shock energy absorber for comfort

Easy and quick maintenance

Window to check disc presence

Noise level at operator, EN 12549: LWA, $1s = 114 \, dB(A) \, / \, LpA$, 1s, $1m = 101 \, dB(A) \, / \, LpA$, 1s, $0 = 105 \, dB(A) \, / \, LpA$

Vibration, EN ISO 8662-11: 6.6 m-s-2

Accessories	Consumables
Magazine	C9, CR9, CR9P, SC9, SBR9, SA9, CT30, C9 Clip A, Formwork Spacer, Shuttering Spacer, CR9TP
Single Shot Pin Guide	C9, SC9 (15 to 60mm collated)
Kit CI 40 to 120	CI-6 & CI-9
Kit SA12-8	SA12-8 + RE 25 to 40

Technical Helpline UK: 0800 731 4924 Technical Helpline ROI: 1 800 882 388